# LYYN EAGLE PORTABLE

# The portable and easy to use LYYN solution for real-time digital video



#### Real-time video enhancement anywhere

Use the Eagle Portable to enhance the live feed from a camera in any existing SDI video system. Enhance a recorded material after fieldwork. Use the Portable wherever you need to see more with video in situations with less than optimal visibility conditions.

#### **Portable**

LYYN Eagle Portable is designed for real portability. It has a solid aluminum casing, large control knobs and runs on 12 V DC.

## Plug and play

Connect the LYYN Eagle Portable between the camera and a monitor or VCR and you are up and running. No complicated installation. No advanced configuration. No onscreen menu trees. Just plug in, turn on and see more.

#### Easy to use

Large knobs for control of enhancement level and size and position of a rectangular selection of the scene. With this simple manual interface, you can focus on your task.

#### Software remote control

The Eagle Portable can be controlled remotely through a standard RS232 serial interface with simple text commands. You can write scripts and/or software on your own control platform for an integrated solution.

### Video standards

Standard	Name	Bit rates	Resolution & frame-rate
SMPTE 292	HD-SDI	1.485 Gbit/s, and 1.485/1.001 Gbit/s	720p, 1080i60
SMPTE 424	3G-SDI	2.970 Gbit/s, and 2.970/1.001 Gbit/s	1080p60

### **Physical connectors**

**Video**: Standard BNC contacts. Use 75  $\Omega$  cabling **Communication**: Micro USB. Integrated FTDI-chip.

#### **Power**

Circular plug: 12 V DC, 1.0 A

<del>-</del>+

or micro USB, 1.0 A

# **Operating conditions**

Temperature:  $0 - 50 \,^{\circ}\text{C} \, (32 - 122 \,^{\circ}\text{F})$ Humidity:  $0 - 80\% \, \text{RH} \, (\text{non-condensing})$ 

#### **Dimensions and weight**

Dimensions: 54x172x184 (HxWxD in mm)

Weight: 925g, excl. power supply

#### Video latency

1 microsecond

#### **Approvals**

CE

US Patent No. 8,023,730 and equivalent patents and patent applications in other countries.

User controls

Lyynification:

- window size

- window position

On/Off

- level

